

BAGGAGE TRACTOR GASOLINE

XT560G

Standard cab enclosure with windshield, wiper kit & rear window protection cage

Increased visibility of the tarmac for drivers

LED lighting

Front and rear towing hitches included



FEATURES & BENEFITS

- Hydraulic steering system
- Front and rear towing couplers with rear cab control
- Standard cab enclosure with windshield and wiper kit
- Digital controller with self-diagnosis function
- Vacuum assist hydraulic braking system

WHY AVRO

- ▶ 2 years / 2000 hours standard warranty
- ▶ Single assigned point of service for maximum uptime
- ▶ Multiple purchase, rental and finance options
- ▶ Dedicated parts distribution North America-wide



LED controller with EMC and water-dust prevention.

AIRCRAFT GROUND SUPPORT SALES AND SERVICE

SPECIFICATIONS

| | |
|----------------|-----------------|
| MODEL | XT560G |
| POWER TYPE | GASOLINE |
| SERVICE WEIGHT | 9921lb (4500kg) |

DIMENSIONS

| | |
|--------------------------------|---|
| SIZE (LENGTH X WIDTH X HEIGHT) | 122" (3090mm) x 57" (1450mm) x 78" (2000mm) |
| WHEELBASE | 63" (1600mm) |
| TOWING COUPLERS HEIGHTS | 12" (305mm) |
| GROUND CLEARANCE | 6" (150mm) |
| TURNING RADIUS | 116" (2950mm) |

TIRES

| | |
|-------------|----------------------------|
| FRONT, REAR | 6.50-10-10PR, 7.00-12-12PR |
|-------------|----------------------------|

PERFORMANCE

| | |
|-------------------------|----------------------|
| SPEED (LOADED/UNLOADED) | L: 15km/h, U: 35km/h |
| FRONT AXLE LOAD | 2640lb (1200kg) |
| REAR AXLE LOAD | 6820lb (3100kg) |
| MAX DRAWBAR PULL | 5600lb (25kN) |

MOTOR

| | |
|----------------------|------------|
| ENGINE MODEL | PSI 2.4 |
| DISPLACEMENT | CC 2967 |
| RATED POWER Kw/rpm | 49.8/2800 |
| RATED TORQUE N-m/rpm | 169.7/2400 |

TRANSMISSION

| | | |
|---------------------|-----------------|-------------|
| MODEL | OKAMURA Y43290 | |
| SHIFT CONFIGURATION | AUTO 2 SHIFTS | |
| GEAR RATIO | FRONT (2 Gears) | 3:07 ; 2:13 |
| | REAR (1 Gear) | 2.4 |
| DRIVE AXLE RATIO | 6.67 | |

CONFIGURATION OPTIONS

| | |
|------|----------------------|
| HEAT | OPTIONAL |
| CAB | OPEN, FULLY ENCLOSED |