

Belt Loader Diesel

BL30D

Standard Collision Avoidance System
(CAS)

Dual belt height adjustment

Variable belt speed



WHY AVRO

- ▶ 2 years / 2000 hours standard warranty
- ▶ Customized business relationship
- ▶ AAA maintenance program
- ▶ Stock locations in the United States and Canada

Features & Benefits

- Hydraulic steering system
- Digital controller with self-diagnosis function
- Hydraulic braking system with redundancy
- Front & Rear Belt Height Adjustment with Variable Belt Speed
- Single or dual bumper option
- Safety interlocks
- Safety steps

AIRCRAFT GROUND SUPPORT EQUIPMENT

Performance	
MODEL	BL30D
MAX SPEED FORWARD	17mph (28km/h)
Engine	
MAKE AND MODEL	CUMMINS 2.8 L4 74hp(55kW)
EMISSIONS	Tier 4F
DEF	Not required
Weight	
SERVICE WEIGHT	8,377lb (3,800kg)
Axel	
CAPACITY - F /R	5300 / 6600 (lb)
Main Dimensions	
HEIGHT WITH CABIN	59" (1,500mm)
OVERALL LENGTH	315" (8,000mm)
OVERALL WIDTH	84" (2,120mm)
WHEEL BASE	118" (3,000mm)
GROUND CLEARANCE	6" (150mm)
TURNING RADIUS	300" (7,600mm)
Tire	
TYPE	Pneumatic
FRONT	225/70 R15
REAR	225/70 R15
Working Range	
TRANSFER LENGHT	301" (7,650mm)
TRANSFER WIDTH	34" (870mm)
CONVEYOR BELT TRANSMISSION SPEED	160 - 500mm/s
CONVEYOR BELT MAX TILT ANGLE	29" (736mm)
TURNING RADIUS	160"/50" (4,100mm/1,260mm)
TRANSFER MINIMUM HEIGHT (F/R)	46"/35" (1,180mm/880mm)
Optional	
SINGLE/DUAL FRONT BUMPERS	
REAR BAR	
CRJ HANDRAIL	
EXTENDABLE HANDRAIL	