

Belt Loader Gasoline

BL30G

Collision Avoidance System (CAS) Dual belt height adjustment Variable belt speed



WHY AVRO

- 2 years / 2000 hours standard warranty
- Customized business relationship
- AAA maintenance program
- Stock locations in the United States and Canada


Features & Benefits

- Hydraulic steering system
- Digital controller with self-diagnosis function
- Hydraulic braking system with redundancy
- Front & Rear Belt Height Adjustment with Variable Belt Speed
- Single or dual bumper option
- Safety interlocks
- Safety steps

AIRCRAFT GROUND SUPPORT EQUIPMENT

AVRO GSE

avrogse.com



PROUDLY SERVING NORTH AMERICA

Belt Loader - Gasoline

Performance	
MODEL	BL30G
MAX SPEED FORWARD	17mph (28km/h)
Engine	
MAKE AND MODEL	PSI 2.4 L4 49.8hp (37kW)
Weight	
SERVICE WEIGHT	9,260lb (4,200kg)
Axle	
CAPACITY - F /R	5,300 / 6,600 (Ib)
Main Dimensions	
HEIGHT WITH CABIN	59" (1,500mm)
OVERALL LENGTH	315" (8,000mm)
OVERALL WIDTH	84" (2,120mm)
WHEEL BASE	118" (3,000mm)
GROUND CLEARANCE	6" (150mm)
TURNING RADIUS	300" (7,600mm)
Tire	
ТҮРЕ	Pneumatic
TYPE FRONT	Pneumatic 225/70 R15
FRONT	225/70 R15
FRONT REAR	225/70 R15
FRONT REAR Working Range	225/70 R15 225/70 R15
FRONT REAR Working Range TRANSFER LENGTH	225/70 R15 225/70 R15 301" (7,650mm)
FRONT REAR Working Range TRANSFER LENGTH TRANSFER WIDTH	225/70 R15 225/70 R15 301" (7,650mm) 34" (870mm)
FRONT REAR Working Range TRANSFER LENGTH TRANSFER WIDTH CONVEYOR BELT TRANSMISSION SPEED	225/70 R15 225/70 R15 301" (7,650mm) 34" (870mm) 160 - 500mm/s
FRONT REAR Working Range TRANSFER LENGTH TRANSFER WIDTH CONVEYOR BELT TRANSMISSION SPEED CONVEYOR BELT MAX TILT ANGLE	225/70 R15 225/70 R15 301" (7,650mm) 34" (870mm) 160 - 500mm/s 29" (736mm)
FRONT REAR Working Range TRANSFER LENGTH TRANSFER WIDTH CONVEYOR BELT TRANSMISSION SPEED CONVEYOR BELT MAX TILT ANGLE TURNING RADIUS	225/70 R15 225/70 R15 301" (7,650mm) 34" (870mm) 160 - 500mm/s 29" (736mm) 160"/50" (4,100mm/1,260mm)
FRONT REAR Working Range TRANSFER LENGTH TRANSFER WIDTH CONVEYOR BELT TRANSMISSION SPEED CONVEYOR BELT MAX TILT ANGLE TURNING RADIUS TRANSFER MINIMUM HEIGHT (F/R)	225/70 R15 225/70 R15 301" (7,650mm) 34" (870mm) 160 - 500mm/s 29" (736mm) 160"/50" (4,100mm/1,260mm)
FRONT REAR Working Range TRANSFER LENGTH TRANSFER WIDTH CONVEYOR BELT TRANSMISSION SPEED CONVEYOR BELT MAX TILT ANGLE TURNING RADIUS TRANSFER MINIMUM HEIGHT (F/R) Optional	225/70 R15 225/70 R15 301" (7,650mm) 34" (870mm) 160 - 500mm/s 29" (736mm) 160"/50" (4,100mm/1,260mm)

EXTENDABLE HANDRAIL

AVRO GSE

PROUDLY SERVING NORTH AMERICA