


# Belt Loader Lead Acid Electric

BL30LA

- Collision Avoidance System (CAS)
- Dual belt height adjustment
- Variable belt speed



## Features & Benefits

- Hydraulic steering system
- Digital controller with self-diagnosis function
- Hydraulic braking system with redundancy
- Front & Rear Belt Height Adjustment with Variable Belt Speed
- Safety interlocks
- Safety steps

## WHY AVRO

- ▶ 2 years / 2000 hours standard warranty
- ▶ Customized business relationship
- ▶ AAA maintenance program
- ▶ Stock locations in the United States and Canada

AIRCRAFT GROUND SUPPORT EQUIPMENT

Performance	
MODEL	BL30LA
MAX SPEED FORWARD	17mph (28km/h)
Powertrain	
POWER TYPE	Lead Acid Battery
OPERATING VOLTAGE	80V
AH CAPACITY	440AH
Axle	
CAPACITY - F/R	5,300 / 6,600 (lb)
Weight	
SERVICE WEIGHT WITH BATTERY	8,400lb (3,800kg)
Main Dimensions	
HEIGHT	59" (1,500mm)
OVERALL LENGTH	315" (8,000mm)
OVERALL WIDTH	84" (2,120mm)
WHEEL BASE	118" (3,000mm)
GROUND CLEARANCE	6" (150mm)
TURNING RADIUS	300" (7,600mm)
Tire	
TYPE	Pneumatic
FRONT	225/70 R15
REAR	225/70 R15
Working Range	
TRANSFER LENGTH	301" (7,650mm)
TRANSFER WIDTH	34" (870mm)
CONVEYOR BELT TRANSMISSION SPEED	160 - 500mm/s
CONVEYOR BELT MAX TILT ANGLE	29" (736mm)
TURNING RADIUS	160"/50" (4,100mm/1,260mm)
TRANSFER MINIMUM HEIGHT (F/R)	46"/35" (1,180mm/880mm)
Optional	
SINGLE/DUAL FRONT BUMPERS	
REAR BAR	
CRJ HANDRAIL	
EXTENDABLE HANDRAIL	