

Tow Tractor

PT600

Standard lifting cab allows for 360-degree operator view (backup camera)

LED lighting

Extended tow hitch for better visibility



Features & Benefits

Deutz engine

Dana axles

4 wheel drive

2WS, 4WS, & CRAB with automatic realignment system

Air conditioning & heating

Winterized kit

Access panels designed for ease of accessibility for maintenance and repairs

Hydraulic cooling system

Common truck tires (lower cost of ownership)



WHY AVRO

- ▶ 2 years or 2000 hours standard warranty
- ▶ Customized business relationship
- ▶ AAA maintenance program
- ▶ Stock locations in the United States and Canada

AIRCRAFT GROUND SUPPORT EQUIPMENT

Performance	
MODEL	PT600
DBP	47,200lbf (210kN)
MAX SPEED F	17mph (27km/h)
Engine	
MAKE AND MODEL	Deutz TCD 4.1 L4 154hp (115kW)
EMISSION	Tier 4F
Transmission	
MAKE AND MODEL	ZF powershift 6F/3R
Weight	
BASIC WEIGHT	52,000lb (23,587kg)
MAX BALLASTED WEIGHT	66,000lb (29,937kg)
Axle	
TYPE	Axle (planetary)
CAPACITY - F/R	16.5/16.5
MOUNT TYPE -F/R	Fix / Pivot
Brakes	
SERVICE	Internal wet hydraulic disc
PARKING	Fail safe spring actuated hydraulically released
Drive	
POWERTRAIN	Fulltime 4WD
TYPE	Orbit hydraulic steering
OPERATION MODES	4WS / 2WS / Crab
MINIMUM TURNING RADIUS	112" (2839mm)
Main Dimensions	
HEIGHT WITH CABIN	80" (2032mm)
OVERHANG FRONT / REAR	95"/33" (2413mm/844mm)
OVERALL LENGTH	255" (6477mm)
OVERALL WIDTH	98" (2489mm)
GROUND CLEARANCE	11" (279mm)
TRACK	76" (1930mm)
Tire (Common Truck Tires)	
TYPE	Pneumatic
FRONT	385/65 R 22.5
REAR	385/65 R 22.5