

Water Cart

WC300G



Features & Benefits

300-gallon stainless steel tank provides maximum capacity with corrosion resistance

Honda GX120 engine with 22 GPM flow delivers proven reliability and fast servicing

Integrated freeze protection includes dual heaters and full insulation

Galvanized steel construction offers superior rust resistance

Anti-crush hose with breakaway ensures equipment protection and operator safety

Precision water meter enables accurate dispensing control

15 mph towing with solid tires allows fast repositioning with puncture-proof reliability

Specifications	
LENGTH (TOWBAR UPRIGHT POSITION)	118.50 in (301 cm)
LENGTH (TOWBAR HORIZONTAL POSITION)	156 in (397 cm)
WIDTH	56.50 in (143.50 cm)
HEIGHT (TOWBAR UPRIGHT POSITION)	53.50 in (136 cm)
HEIGHT (TOWBAR HORIZONTAL POSITION)	46.50 in (118 cm)
WEIGHT	1,540 lb (698 kg)
FILL TANK CAPACITY	300 gal (1,135 l)
FLOW RATE	22 G.P.M. @ 40 psi (83 L.P.M. @ 40 psi)
MAX SPEED LIMIT	15 mph (25 kph)
TIRES	4.00 x 8 Solid

WHY AVRO

- 2 years standard warranty
- Customized business relationship
- AAA maintenance program
- Stock locations in the United States and Canada

AIRCRAFT GROUND SUPPORT EQUIPMENT

AVRO GSE avrogse.com



PROUDLY SERVING NORTH AMERICA