



Water Cart

WC300G





Features & Benefits

- 300-gallon stainless steel tank provides maximum capacity with corrosion resistance
- Honda GX120 engine with 22 GPM flow delivers proven reliability and fast servicing
- Integrated freeze protection includes dual heaters and full insulation
- Galvanized steel construction offers superior rust resistance
- Anti-crush hose with breakaway ensures equipment protection and operator safety
- Precision water meter enables accurate dispensing control
- 15 mph towing with solid tires allows fast repositioning with puncture-proof reliability

Specifications

LENGTH (TOWBAR UPRIGHT POSITION)	118.50 in (301 cm)
LENGTH (TOWBAR HORIZONTAL POSITION)	156 in (397 cm)
WIDTH	56.50 in (143.50 cm)
HEIGHT (TOWBAR UPRIGHT POSITION)	53.50 in (136 cm)
HEIGHT (TOWBAR HORIZONTAL POSITION)	46.50 in (118 cm)
WEIGHT	1,540 lb (698 kg)
FILL TANK CAPACITY	300 gal (1,135 l)
FLOW RATE	22 G.P.M. @ 40 psi (83 L.P.M. @ 40 psi)
MAX SPEED LIMIT	15 mph (25 kph)
TIRES	4.00 x 8 Solid



WHY AVRO

- ▶ 1-year standard warranty
- ▶ AAA maintenance program
- ▶ Customized business relationship
- ▶ Made in North America