

Towable Belt Loader 6 Meters EV

TB20E



Features & Benefits

- 48V electric system for quiet, eco-friendly operation
- Towbar-controlled hydrostatic drive for precise maneuvering
- Adjustable belt speed up to 48 m/min for faster turnaround
- Six-meter belt length to service a range of aircraft
- Three-meter maximum height for efficient loading and unloading
- Durable wheel options to handle various ramp surfaces

WHY AVRO

- ▶ 2 years / 2000 hours standard warranty
- ▶ Customized business relationship
- ▶ AAA maintenance program
- ▶ Stock locations in the United States and Canada

AIRCRAFT GROUND SUPPORT EQUIPMENT

Specifications	
MODEL	TB20E
ALIMENTATION	Electric – Pedestrian control from the towbar
ENGINE	Best Motors
NOMINAL POWER	7 kW / 48 V
MAX HEIGHT	118.11 in (3,000 mm)
BELT WIDTH	23.62 in (600 mm)
BELT LENGTH	236.22 in (6,000 mm)
WHEEL BASE	118" (3,000mm)
SIDE REMOVABLE PROTECTION	Optional on demand
BELT SPEED	Adjustable
MAX BELT SPEED	48 m/min
WEIGHT	3,306.93 in (1,500 kg)
TRASLACION	Hydrostatic from the tow bar
TOWBAR EYE	ø40 DIN 74054
PARKING BRAKE	Mechanic
NUMBER OF BRAKING AXLES	1
BATTERY	48 Volt – 260 Ah
WHEELS TYPE	Pneumatic Superelastic (optional)
WHEELS	2 FRONT (4.00-8") 2 REAR (4.00-8")
CE CONFORMITY	DIR. 2006/42/CE ("DIRECTIVE ON MACHINERY") DIR. 2004/108/CE IATA AHM 925