

Ground Power Unit Diesel

28V DC

● Features & Benefits

- Delivers 2000A peak output for quick engine starts
- Provides 800A continuous power for stable operation
- Maintains precise voltage within $\pm 1\%$ range
- Meets MIL-STD-704F standards for aircraft safety
- Operates reliably in temperatures from -20°C to $+45^{\circ}\text{C}$.
- Minimizes noise with a soundproof canopy at 72 dB
- Allows easy ramp transport with a trailer design
- Offers clear monitoring with a control panel and alarms
- Ensures safety with protection against oil, temperature, and voltage issues
- Adapts to needs with optional electric start and plug protection



WHY AVRO

- ▶ 2 years standard warranty
- ▶ AAA maintenance program
- ▶ Customized business relationship
- ▶ Stock locations in the United States and Canada

AIRCRAFT GROUND SUPPORT EQUIPMENT

Technical Data

Output Voltage	28V DC
GPU performance	800 A continuous / 1,200 A for 10 sec. / 2,000 A for 5 sec.
Output available	Nº1 x 28V DC cable length 10 meters
Engine	Diesel engine, 4 strokes, water cooled
Rated speed	1,800 rpm
Configuration	Slow towing trailer
Max towing speed	30km/h
Fuel tank capacity	185 l

Dimensions

Length (L)	3,120 mm – towbar up
Width (W)	1,680 mm
Height (H)	1,660 mm (beacon included)
Weight	2,000 kg