

Towable Belt Loader

TB20G TB20D TB20E



Features & Benefits

- 48V electric system for quiet, eco-friendly operation
- Towbar-controlled hydrostatic drive for precise maneuvering
- Adjustable belt speed up to 48 m/min for faster turnaround
- Six-meter belt length to service a range of aircraft
- Three-meter maximum height for efficient loading and unloading
- Durable wheel options to handle various ramp surfaces

WHY AVRO

- ▶ 2 years / 2000 hours standard warranty
- ▶ Customized business relationship
- ▶ AAA maintenance program
- ▶ Stock locations in the United States and Canada

AIRCRAFT GROUND SUPPORT EQUIPMENT

	TB20G	TB20D	TB20E
Specifications			
ALIMENTATION	Gas	Diesel	Electric
ENGINE	Honda or similar	Yanmar or similar	Best Motors
NOMINAL POWER	20 kW	20 kW	7 kW/48 V
MAX HEIGHT		118.11 in (3,000 mm)	
BELT WIDTH		23.62 in (600 mm)	
BELT LENGTH		236.22 in (6,000 mm)	
WHEEL BASE		118" (3,000mm)	
SIDE REMOVABLE PROTECTION		Optional on demand	
BELT SPEED		Adjustable	
MAX BELT SPEED		48 m/min	
WEIGHT		3,306.93 in (1,500 kg)	
TRASLACION		Hydrostatic from the tow bar	
TOWBAR EYE		ø40 DIN 74054	
PARKING BRAKE		Mechanic	
NUMBER OF BRAKING AXLES		1	
BATTERY		48 Volt – 260 Ah	
WHEELS TYPE		Pneumatic Superelastic (optional)	
WHEELS		2 FRONT (4.00-8") 2 REAR (4.00-8")	
CE CONFORMITY		DIR. 2006/42/CE ("DIRECTIVE ON MACHINERY") DIR. 2004/108/CE IATA AHM 925	