avro GSE
Best on Ground

Lavatory Cart

LC250G





Features & Benefits

- Dual tank system (150 gal waste / 100 gal fresh) provides optimal capacity ratio with fewer trips required
- Flexible waste valve configuration offers ground, side, or rear discharge options
- Honda GX120 engine with 22 GPM fresh water delivers reliable delivery with precision metering
- Complete freeze protection package includes tank and pump heaters with full insulation
- Isolated waste/fresh systems prevents cross-contamination and ensures regulatory compliance
- Heavy-Duty Galvanized Construction provides corrosion resistance and extended service life
- Anti-crush hoses with safety couplings prevents damage and protects operators

Specifications

LENGTH (TOWBAR UPRIGHT POSITION)	118.50 in (301 cm)
LENGTH (TOWBAR HORIZONTAL POSITION)	156 in (397 cm)
WIDTH	56.50 in (143.50 cm)
HEIGHT (TOWBAR UPRIGHT POSITION)	53.50 in (136 cm)
HEIGHT (TOWBAR HORIZONTAL POSITION)	46.50 in (118 cm)
WEIGHT	1,600 lb (726 kg)
FLUSH TANK CAPACITY	100 gal (378 l)
WASTE TANK CAPACITY	150 gal (568 l)
FLOW RATE	22 G.P.M. @ 40 psi (83 L.P.M. @ 40 psi)
MAX SPEED LIMIT	15 mph (25 kph)
TIRES	4.00 x 8 Solid





WHY AVRO

- 1-year standard warranty
- Customized business relationship
- AAA maintenance program
- Made in North America

avrogse.com
parts@avrogse.com
service@avrogse.com
+1 833 220 2810